



TECHNICAL DATA

GB INTERCOOLER SDX 15W-40

APPLICATIONS

GB INTERCOOLER SDX 15W-40 is a semi-synthetic heavy duty diesel engine oil formulated using the highest quality synthetic and virgin mineral base oils together with enhanced additive systems for use in heavy-duty diesel engines in severe on and off-highway applications. Whilst meeting the requirements of both Euro IV and Euro V engines, it is not compatible with Diesel Particulate Trap Filters.

PERFORMANCE FEATURES

GB INTERCOOLER SDX 15W-40 has been developed for use in heavy duty diesel engines and offers the following features:

- Excellent anti-wear protection
- Rust and corrosion protection
- Effective control of soot, sludge and piston deposits
- Excellent oxidation and thermal stability
- Extended drain capability

PERFORMANCE DETAILS

GB INTERCOOLER SDX 15W-40 may be used where the following specifications are required:

ACEA A3/B3/B4/E3/E5/E7	MACK EO-M PLUS
API CI-4/CH-4/CG-4/CF-4/CF/SJ/SL	MAN M 3275
ALLISON C-4	MERCEDES BENZ p228.1/228.3/229.1
CATERPILLAR ECF-1	MTU Type 2
CUMMINS CES 20071/72/76/77/78	RENAULT VI RLD-2
GLOBAL DHD-1	VOLVO VDS-3

Cont'd .../...

GB LUBRICANTS

Albany Road Gateshead NE8 3BP
Tel: 0191 490 4312
Fax: 0191 477 9544
e-mail: gblsales@gb-lubricants-fuels.co.uk
www.gb-lubricants-fuels.co.uk

A division of Goodall Bates & Todd Ltd



Q 06093
ISO 9001



EMS 72776
ISO 14001



OHS 88475
OHSAS 18001

GB LUBRICANTS

CHARACTERISTICS

TEST	UNIT	METHOD	TYPICAL PHYSICAL CHARACTERISTICS
SAE			15W-40
Appearance	-	-	Clear amber liquid
Density @ 15°C	kg/m ³	IP 160	882
Kinematic Viscosity @ 40°C	cSt	IP 71	99.2
Kinematic Viscosity @ 100°C	cSt	IP 71	13.8
Viscosity Index	-	IP 226	140
Flash Point	°C	IP 34	208

STORAGE AND HANDLING

GB INTERCOOLER SDX 15W-40 should be stored under cover to avoid water collecting in the rim of upturned barrels.

HEALTH, SAFETY AND THE ENVIRONMENT

Further information on GB INTERCOOLER SDX 15W-40 can be obtained by referring to the corresponding Material Safety Data Sheet.

For guidance on storage and handling of all lubricants and related products, GB Lubricants recommend the Environment Agency, www.environment-agency.gov.uk, as an excellent source of advice.

If you have any queries, please do not hesitate to contact either your local Technical Sales Representative or our Technical Department.

The Company policy is to ensure that a range of products is supplied which complies with the latest specifications and codes within the relevant industry. As part of this development process, we therefore reserve the right to amend formulations and specifications, without prior notice.