



TECHNICAL DATA

GB UNIMOT® 5 10W-40

APPLICATIONS

GB UNIMOT® 5 10W-40 is a fully synthetic heavy-duty diesel engine oil formulated using the highest quality synthetic base oils and enhanced additive systems for use in heavy-duty diesel engines in severe on- and off-highway applications. Whilst meeting the requirements of both Euro IV and Euro V engines, it is not compatible with Diesel Particulate Trap Filters.

PERFORMANCE FEATURES

GB UNIMOT® 5 10W-40 has been developed for use in heavy-duty diesel engines and offers the following features:

- Excellent anti-wear protection
- Rust and corrosion protection
- Effective control of soot, sludge and piston deposits
- Excellent oxidation and thermal stability
- Improved fuel economy
- Extended drain capability

PERFORMANCE DETAILS

The following Original Equipment Manufacturers' formal approvals have been obtained:

MB - Approval 228.5 RENAULT VI RLD-2/RXD	SCANIA LDF VOLVO VDS-3
---	---------------------------

GB UNIMOT® 5 10W-40 may be used where the following specifications are required:

ACEA E4/E7 API CF	CUMMINS CES 20072 MAN M 3277	MTU Type 3
----------------------	---------------------------------	------------

Cont'd .../...

GB LUBRICANTS

Albany Road Gateshead NE8 3BP
Tel: 0191 490 4312
Fax: 0191 477 9544
e-mail: gblsales@gb-lubricants-fuels.co.uk
www.gb-lubricants-fuels.co.uk

A division of Goodall Bates & Todd Ltd



Q 06093
ISO 9001



EMS 72776
ISO 14001



OHS 88475
OHSAS 18001

CHARACTERISTICS

TEST	UNIT	METHOD	TYPICAL PHYSICAL CHARACTERISTICS
SAE			10W-40
Appearance	-	-	Amber liquid
Kinematic Viscosity @ 100°C	cSt	ASTM D 445	13.4
Kinematic Viscosity @ 40°C	cSt	ASTM D 445	89.1
Viscosity Index	-	ASTM D 2270	152
Density @ 15°C	kg/m ³	ASTM D 4052	866
CCS @ -25°C	cP	ASTM D 5293	6520
HTHS Viscosity	cP	ASTM D 4683	3.81
Noack	%	CEC-L-40	9.5
Total Base Number	mg KOH/g	ASTM D 2896	15.8
Sulphated Ash	mass %	ASTM D 874	1.9
Flash Point	°C	ASTM D 93	206
Pour Point	°C	ASTM D 5940	-48

STORAGE AND HANDLING

GB UNIMOT® 5 10W-40 should be stored under cover to avoid water collecting in the rim of upturned barrels.

HEALTH, SAFETY AND THE ENVIRONMENT

Further information on GB UNIMOT® 5 10W-40 can be obtained by referring to the corresponding Material Safety Data Sheet.

For guidance on storage and handling of all lubricants and related products, GB Lubricants recommend the Environment Agency, www.environment-agency.gov.uk, as an excellent source of advice.

If you have any queries, please do not hesitate to contact either your local Technical Sales Representative or our Technical Department.

The Company policy is to ensure that a range of products is supplied which complies with the latest specifications and codes within the relevant industry. As part of this development process, we therefore reserve the right to amend formulations and specifications, without prior notice.